

N-E90 Pro



Finger



RFID



Inbuilt Battery



WiFi



LAN



USB



Access Control

Time Attendance and Access Control

Storage Capacity

Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	1,50,000

Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



N-E90 Pro

Communication Interface

Communication	Wi-Fi, TCP/IP, USB
---------------	--------------------

Biometric

Push Data	Yes
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Durable and Rigid Body



Unaffected by High
Temperatures 0° ~ 50°

Audio/Visual

LCD	2.4" TFT colour screen 320X240 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay	Yes
Support	Remote, Push Button, No Touch

Power & Environment

Inbuilt Battery Backup	Yes
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	180 x 130 x 45 mm

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control